



999.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron-M/Pentium-M
- Integr. Autostart Controller
- Integr. Automotive power

**Support:**  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

The CALU-M(2)C-Series has an integrated car-power supply (direct connectable to car battery and ignition plus + integrated automatic Start/Stop-Controller.

The time intervals for automatic Start and Stop can be adjusted in the BIOS of the PC !

**CALU specifications**

|                              |                                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Processor (supported)</b> | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher                                                                                                                                                                                                                                                                                                                          |
| <b>Memory</b>                | Supports DDR 333/266 DIMM RAM<br><br>0.8" low profile<br><br>2x memory slots !<br><br>Maximum : 2 GB                                                                                                                                                                                                                                                                                                          |
| <b>Video</b>                 | Intel Extreme Graphics 2<br><br>Supports up to 64MB DVMT video memory                                                                                                                                                                                                                                                                                                                                         |
| <b>Audio</b>                 | Software AC '97 Audio CODEC                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Peripheral Connection</b> | Front :<br><br>1 x IEEE 1394 Firewire port<br><br>1 x USB 2.0 / 1.1 Port<br><br>1 x MIC Port<br><br>1 x Ear Phone output Jack<br><br>Power-on button<br><br>Reset button<br><br>Power-on and HDD LED<br><br><br>Rear :<br><br>1 x RS232 COM port<br><br>1 x parallel printer port<br><br>1 x RJ45 10/100Mb Fast Ethernet<br><br>1 x Line-Out output Jack<br><br>2 x USB 2.0 / 1.1 Ports<br><br>1 x 15 pin VGA |

|                          |                                            |
|--------------------------|--------------------------------------------|
| <b>Storage</b>           | One 2.5 inch Hard Disk and 9.5mm high.     |
|                          | (Support Ultra DMA 33/66/100).             |
| <b>Weight &amp; Size</b> | System approximately 3kg (fully equipped). |
|                          | System Dimension: 155 x 255 x 55 mm        |
| <b>Power req.</b>        | 9-16V, 5A                                  |

**Accessory**

|                        |                                                                |
|------------------------|----------------------------------------------------------------|
| <b>Storage</b>         | Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo |
|                        | Supports all 2.5" standard IDE hard drive, ATA-100/66/33.      |
| <b>Scope of supply</b> | Connector cable for Plus, ignition plus and ground             |
|                        | Barebone                                                       |
|                        | CPU Kühlkörper                                                 |

Installation Tutorial : [Support / Manuals](#)

Graphics driver for 800x480 resolution : [Here](#)